

1362**Description**

This double-sided tape consists of a textile carrier which is layered on both sides with modified dispersion acrylate adhesive. The adhesives is largely resistant to plasticisers. The adhesive on the covered side of the tape has excellent permanent adhesive qualities. The adhesive on the open side allows easy removal without residues from many surfaces. The adhesive is lined with a double sided, white siliconised paper.

Carrier

Rayon

Liner

Siliconised paper, white, 90 g/m²

Adhesive

Modified dispersion acrylate

Area of use

This double-sided tape is especially suitable for the installation of carpets at exhibitions (with high cohesion and easy removal). It is also suited for PVC floors and carpets with PVC backsides.

Technical data

Thickness* (adhesive + carrier)	290 micron		
Temperature resistance***	-20°C to + 100°C		
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)		Covered side:	Open side:
	after 1 min:	13 N/25mm	7 N/25mm
	after 20 min:	15 N/25mm	7 N/25mm
	after 24 h:	16 N/25mm	8 N/25mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)		Covered side:	Open side:
	at 23°C	2 h	5 h
	at 70°C	5 min	10 min
Shelf life**	2 years		
Application temperature	> + 15°C		

* average

** in original packaging, at 20°C and 50% relative humidity

*** 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

